

We claim:

- 5
1. A process for purification of ethylene oxide by distillation, comprising the step in which
- 10
- an aqueous mixture comprising ethylene oxide, formaldehyde and at least 5% by weight of water is introduced via a feed into a distillation apparatus comprising at least one distillation column, the mixture being introduced at a height above the bottom of at least 8 theoretical stages,
  - the ethylene oxide is taken off at the top and
  - 15
  - in the bottom phase, a mixture is obtained which contains less than 5% by weight of ethylene oxide.
- 20
2. A process for purification of ethylene oxide by distillation, comprising the step in which
- 25
- an aqueous mixture comprising ethylene oxide, formaldehyde and at least 5% by weight of water is introduced via a feed into a distillation apparatus comprising at least one packed column which contains a structured or bulk packing and has a specific mass transfer area A, the mixture being introduced at a height above the bottom of at least  $x_{min}$  (in m) which, for a given specific mass transfer area A (in  $m^2/m^3$ ), is given by the equation
- $$x_{min} = 5.5 m - A \cdot 0.006 m^2,$$
- 30

- the ethylene oxide is taken off at the top and

- in the bottom phase a mixture is obtained which contains less than 5% by weight of ethylene oxide.

5

3. A process as claimed in claim 2, wherein the aqueous mixture is introduced via the feed at a height of from  $1.5 X_{min}$  to  $7 X_{min}$ .

4. A process as claimed in claim 2 or 3, wherein the specific mass transfer area  $A$  is in the range from  $100 \text{ m}^2/\text{m}^3$  to  $500 \text{ m}^2/\text{m}^3$ .

10

5. A process as claimed in claim 1, wherein the aqueous mixture comprising ethylene oxide, formaldehyde and at least 5% by weight of water is introduced via a feed into a distillation apparatus comprising at least one plate column, the mixture being introduced at a height above the bottom of at least 12 plates.

15

6. A process as claimed in one of the claims 1 to 5 which further comprises the step in which a further mixture, principally comprising water, is additionally introduced via a feed line at a height of at least one theoretical stage or plate above the feed of the aqueous mixture.

20

7. A process as claimed in one of the claims 1 to 6, wherein flame-arresting packings are used in the distillation apparatus.

25

8. A process as claimed in one of the claims 1 to 7, wherein a distillation apparatus is used in which, between the feed and the bottom, there is installed a side take-off via which is taken off a mixture which is enriched with acetaldehyde in comparison with the influent aqueous mixture.

30

9. A process as claimed in one of the claims 1 to 8; wherein a distillation apparatus is used in which an intermediate reboiler is situated between the feed and the bottom.

5 10. An apparatus for carrying out the process as claimed in one of the claims 7 or 9, comprising a distillation column having a feed (1) at a height above the bottom (4) of at least 8 theoretical stages or, in a plate column, of at least 12 plates above the bottom, a top take-off (3), optionally a side take-off (5), and flame-arresting packings and, optionally, an intermediate reboiler between  
10 feed (1) and bottom (4).